

IFW 6340 IX UK

12NC/Fx: F102670

GTIN (EAN) code: 8050147026700

DIMENSION	ENSION MEAS	
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mm
Space in front, which is required to install bottom trim	9	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	40	mm
Minimum area for inbound ventilation cavity (tall cabinet)	150	cm ²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	150	cm ²
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	40	mm
Minimum area for inbound ventilation cavity (base cabinet)	150	cm ²
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	150	cm ²

Height of the front 595 mm Width of the front 595 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm Maximum depth all protruding elements, e.g. handles, controls 39 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance in height is adjustable When product panel is missing, set to 0 97 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 480 mm dimension 481 mm Frontal handle thickness 21 mm Frontal handle thickness 21 mm Frontal handle thickness 21 mm MAX Height of the product body 570 mm MAX Height of the product body 570 mm Width of the product body 570 mm Width of the product body 570 mm MAX Height of product body 570 mm MAX Height of product excluding protruding interface elements 570 mm mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Appliance Flap door Projection of front in relation to bearing area mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when flap door is opened totally Appliance of the retrace 525 mm	DIMENSION M		EASURE	
Width of the front 20 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm neighbour front more than 90 degrees 20 mm Projection of front in relation to housing of appliance 20 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable 30 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 40 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 40 mm Height from bearing area of appliances and lower handle 438 mm Frontal handle thickness 21 mm Frontal handle thickness 21 mm MIN Height of the product body 570 mm MAX Height of the product body 570 mm Moth of the product body 570 mm Moth of the product body 570 mm Upeth of the product body 570 mm Pull depth of product excluding protruding interface elements 570 mm - mm - mm - mm - mm - mm - mm - mm	APPLIANCE			
Depth of the front Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width MINI Height of the product body MAX Height of the product body Depth of the product body Depth of the product body Sam may be product body Full depth of product excluding protruding interface elements - mm - mm - mm - mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of front incl. controls when door is opened totally. At the side where the hinge is mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Height of the front	595	mm	
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width 519 mm MIN Height of the product body 570 mm MAX Height of the product body 571 mm Depth of the product body 572 mm Full depth of product excluding protruding interface elements - mm - mm - mm - mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width S19 mm MIN Height of the product body Mith of the product body T70 mm MXHeight of the product body S58 mm Depth of the product body S59 mm Full depth of product excluding protruding interface elements T00 mm T10	Depth of the front	20	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance 20 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 projection of front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle frontal handle thickness 21 mm Frontal handle thickness 21 mm Frontal handle thickness 21 mm MINI Height of the product body 570 mm MAX Height of the product body 570 mm Width of the product body 570 mm Width of the product body 570 mm Full depth of product body 570 mm Full depth of product excluding protruding interface elements 570 mm 570	Maximum depth all protruding elements, e.g. handles, controls	39	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width 519 mm MIN Height of the product body MAX Height of the product body Width of the product body 570 mm Width of the product body 548 mm Full depth of product excluding protruding interface elements - mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 9 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	· · ·	55	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width 519 mm MIN Height of the product body MAX Height of the product body Moxidth of the product body 550 mm Moxidth of the product body 558 mm Depth of the product body 548 mm Full depth of product excluding protruding interface elements - mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Projection of front in relation to housing of appliance	20	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width 519 mm MIN Height of the product body MAX Height of the product body 570 mm Width of the product body 558 mm Depth of the product body 548 mm Full depth of product excluding protruding interface elements - mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm		5	mm	
dimension Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Frontal handle thickness 21 mm Frontal handle width 519 mm MIN Height of the product body 570 mm Width of the product body 570 mm Width of the product body 558 mm Depth of the product body 558 mm Full depth of product excluding protruding interface elements 570 mm	When product panel is missing, set to 0	97	mm	
Frontal handle thickness 21 mm Frontal handle width 519 mm MIN Height of the product body 570 mm MAX Height of the product body 570 mm Width of the product body 570 mm Width of the product body 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding interface elements 570 mm Unit of the product excluding protruding i		460	mm	
Frontal handle width 519 mm MIN Height of the product body 570 mm MAX Height of the product body 570 mm Width of the product body 558 mm Depth of the product body 548 mm Full depth of product excluding protruding interface elements 570 mm mm mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Appliance Side swing door 0 mm Appliance Side swing door 1 controls when door is opened totally. At the side where the hinge is mounted 1 controls opened totally 2 controls opened totally 3 controls opened totally 4 controls opened 5 contro	Height from bearing area of appliances and lower handle	438	mm	
MIN Height of the product body 570 mm MAX Height of the product body 570 mm Width of the product body 558 mm Depth of the product body 548 mm Full depth of product excluding protruding interface elements 570 mm mm mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door 1 mm Appliance Side swing door 1 controls when door is opened totally. At the side where the hinge is momental atteral projection of opened front at the side where the hinge is 1 mm Appliance other 1 mm Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Frontal handle thickness	21	mm	
MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements - mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 570 mm 584 mm 790 mm 490 mm Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Frontal handle width	519	mm	
Width of the product body Depth of the product body Full depth of product excluding protruding interface elements - mm mm mm mm mm mm mm Appliance Can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance Other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	MIN Height of the product body	570	mm	
Depth of the product body Full depth of product excluding protruding interface elements 570 mm	MAX Height of the product body	570	mm	
Full depth of product excluding protruding interface elements - mm - m	Width of the product body	558	mm	
- mm	Depth of the product body	548	mm	
- mm	Full depth of product excluding protruding interface elements	570	mm	
- mm	-	-	mm	
- mm		-	mm	
- mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No - Appliance Flap door - Projection of the opened flap in relation to bearing area 0 mm - Maximum angle when flap door is opened totally 89 mm - Appliance Side swing door - Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted - Lateral projection of opened front at the side where the hinge is fixed 0 mm - Maximum angle when door is opened totally 0 mm - Appliance other - Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Omm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace - mm Appliance In mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace - mm Appliance In mm		-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	-	-	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm		-	mm	
Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Appliance Flap door			
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Projection of the opened flap in relation to bearing area	0	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Maximum angle when flap door is opened totally	89	mm	
mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Appliance Side swing door			
Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm		0	mm	
Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 428 mm	Maximum angle when door is opened totally	0	mm	
·	Appliance other			
Height from niche to bottom end of freespace for the retrace 525 mm	Depth from front end of the niche to the front end of the freespace of the retrace	428	mm	
	Height from niche to bottom end of freespace for the retrace	525	mm	