

## **IFW 6330 WH UK**

12NC/Fx: F102675

## GTIN (EAN) code: 8050147026755

DIMENSION	MEAS	UR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mm
Space in front, which is required to install bottom trim	9	mn
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mn
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	40	mn
Minimum area for inbound ventilation cavity (tall cabinet)	150	cm
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	150	cm
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	40	mm
Minimum area for inbound ventilation cavity (base cabinet)	150	cm
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	150	cm

PPLIANCE sight of the front dth of the front epth of the front eximum depth all protruding elements, e.g. handles, controls teral clearance between front edge and most protruding elements which avoid to open a ighbour front more than 90 degrees ojection of front in relation to housing of appliance	595 595 20 39 55	mm mm mm mm
oth of the front epth of the front extraction of the front edge and most protruding elements which avoid to open a eighbour front more than 90 degrees eighbour front in relation to housing of appliance	595 20 39 55	mm mm mm
epth of the front aximum depth all protruding elements, e.g. handles, controls teral clearance between front edge and most protruding elements which avoid to open a ighbour front more than 90 degrees ojection of front in relation to housing of appliance	20 39 55	mm mm mm
Asximum depth all protruding elements, e.g. handles, controls teral clearance between front edge and most protruding elements which avoid to open a ighbour front more than 90 degrees ojection of front in relation to housing of appliance	39 55 20	mm mm
teral clearance between front edge and most protruding elements which avoid to open a ighbour front more than 90 degrees ojection of front in relation to housing of appliance	55 20	mm
teral clearance between front edge and most protruding elements which avoid to open a ighbour front more than 90 degrees ojection of front in relation to housing of appliance	20	
•		mm
	5	
ojection of front in relation to bearing area of the appliance. Taken at minimum height of pliance, if height is adjustable		mm
nen product panel is missing, set to 0	97	mm
ace in front, which is required to guarantee full operability. The most protruding part gives this nension	460	mm
eight from bearing area of appliances and lower handle	438	mm
ontal handle thickness	21	mm
ontal handle width	519	mm
N Height of the product body	570	mm
AX Height of the product body	570	mm
dth of the product body	558	mm
epth of the product body	548	mm
Il depth of product excluding protruding interface elements	570	mm
	-	mm
pliance can be used as base for other appliances from the same manufacturer. Default is "No"	No	
ppliance Flap door		
ojection of the opened flap in relation to bearing area	0	mm
aximum angle when flap door is opened totally	89	mm
ppliance Side swing door		
teral projection of front incl. controls when door is opened totaly. At the side where the hinge is bunted	0	mm
teral projection of opened front at the side where the hinge is fixed	0	mm
aximum angle when door is opened totally	0	mm
ppliance other		
epth from front end of the niche to the front end of the freespace of the retrace	428	mm
eight from niche to bottom end of freespace for the retrace	525	mm