



| DIMENSION  | MEASURE |                 | DIMENSION   | MEASURE |    |
|--|---------|-----------------|---|---------|----|
| <b>OVERALL CABINET</b>   |         |                 | <b>APPLIANCE</b>  |         |    |
| MIN Height of the wall cabinet niche, including all required space for installation or ventilation | 0       | mm              | Height of the front   | 0       | mm |
| MIN Height of the tall cabinet niche, including all required space for installation or ventilation | 870     | mm              | Width of the front  | 595     | mm |
| MIN Height of the base cabinet niche, including all required space for installation or ventilation | 0       | mm              | Depth of the front  | 25      | mm |
| MAX Height of the wall cabinet niche, including all required space for installation or ventilation | 0       | mm              | Maximum depth all protruding elements, e.g. handles, controls   | 0       | mm |
| MAX Height of the tall cabinet niche, including all required space for installation or ventilation | 0       | mm              | Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees    | 0       | mm |
| MAX Height of the base cabinet niche, including all required space for installation or ventilation | 0       | mm              | Projection of front in relation to housing of appliance   | 0       | mm |
| MIN Width of the wall cabinet niche, including all required space for installation or ventilation  | 0       | mm              | Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable | 0       | mm |
| MIN Width of the tall cabinet niche, including all required space for installation or ventilation  | 562     | mm              | When product panel is missing, set to 0   | 115     | mm |
| MIN Width of the base cabinet niche, including all required space for installation or ventilation  | 0       | mm              | Space in front, which is required to guarantee full operability. The most protruding part gives this dimension                  | 0       | mm |
| MAX Width of the wall cabinet niche, including all required space for installation or ventilation  | 0       | mm              | Height from bearing area of appliances and lower handle   | 0       | mm |
| MAX Width of the tall cabinet niche, including all required space for installation or ventilation  | 0       | mm              | Frontal handle thickness  | 0       | mm |
| MAX Width of the base cabinet niche, including all required space for installation or ventilation  | 562     | mm              | Frontal handle width  | 513     | mm |
| MIN Depth of the wall cabinet niche, including all required space for installation or ventilation  | 0       | mm              | MIN Height of the product body  | 0       | mm |
| MIN Depth of the tall cabinet niche, including all required space for installation or ventilation  | 0       | mm              | MAX Height of the product body  | 867     | mm |
| MIN Depth of the base cabinet niche, including all required space for installation or ventilation  | 0       | mm              | Width of the product body   | 0       | mm |
| Space in front, which is required to install bottom trim   | 0       | mm              | Depth of the product body   | 0       | mm |
| Indicates whether a ventilation opening is needed or not. Default is "N"                           | Yes     |                 | Full depth of product excluding protruding interface elements   | 0       | mm |
| <b>WALL CABINET (vent-shaft incoming)</b>  |         |                 | MIN depth between plinth return and front   | 0       | mm |
| Indicates the position of the freespace for the inbound airflow (wall cabinet)                     | Rear    |                 | MAX depth between plinth return and front   | 0       | mm |
| Minimum space or inbound ventilation (wall cabinet)  | 0       | mm              | Height MIN Plinth return. This dimension is taken by minimum appliance height   | 0       | mm |
| Minimum area for inbound ventilation cavity (wall cabinet)   | 0       | cm <sup>2</sup> | Height MAX Plinth return. This dimension is taken at maximum appliance height   | 0       | mm |
| <b>WALL CABINET (vent-shaft outgoing)</b>  |         |                 | Appliance can be used as base for other appliances from the same manufacturer. Default is "No"                                  | No      |    |
| Indicates the position of the freespace for the outbound airflow (wall cabinet)                    | Rear    |                 | <b>Appliance Flap door</b>  |         |    |
| Minimum space or outbound ventilation (wall cabinet)   | 0       | mm              | Projection of the opened flap in relation to bearing area   | 5       | mm |
| Minimum area for outbound ventilation cavity (wall cabinet)  | 0       | cm <sup>2</sup> | Maximum angle when flap door is opened totally  | 89      | mm |
| <b>TALL CABINET (vent-shaft incoming)</b>  |         |                 | <b>Appliance Side swing door</b>  |         |    |
| Indicates the position of the freespace for the inbound airflow (tall cabinet)                     | Rear    |                 | Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted                  | 0       | mm |
| Minimum space for inbound ventilation (tall cabinet)   | 50      | mm              | Lateral projection of opened front at the side where the hinge is fixed   | 0       | mm |
| Minimum area for inbound ventilation cavity (tall cabinet)   | 281     | cm <sup>2</sup> | Maximum angle when door is opened totally   | 0       | mm |
| <b>TALL CABINET (vent-shaft outgoing)</b>  |         |                 | <b>Appliance other</b>  |         |    |
| Indicates the position of the freespace for the outbound airflow (tall cabinet)                    | Rear    |                 | Depth from front end of the niche to the front end of the freespace of the retrace  | 0       | mm |
| Minimum space for outbound ventilation (tall cabinet)  | 0       | mm              | Height from niche to bottom end of freespace for the retrace  | 849     | mm |
| Minimum area for outbound ventilation cavity (tall cabinet)  | 281     | cm <sup>2</sup> |   |         |    |
| <b>BASE CABINET (vent-shaft incoming)</b>  |         |                 |   |         |    |
| Indicates the position of the freespace for the inbound airflow (base cabinet)                     | Rear    |                 |   |         |    |
| Minimum space for inbound ventilation (base cabinet)   | 0       | mm              |   |         |    |
| Minimum area for inbound ventilation cavity (base cabinet)   | 0       | cm <sup>2</sup> |   |         |    |
| <b>BASE CABINET (vent-shaft outgoing)</b>  |         |                 |   |         |    |
| Indicates the position of the freespace for the outbound airflow (base cabinet)                    | Rear    |                 |   |         |    |
| Minimum space for outbound ventilation (base cabinet)  | 0       | mm              |   |         |    |
| Minimum area for outbound ventilation cavity (base cabinet)  | 0       | cm <sup>2</sup> |   |         |    |