# N 30, Built-in oven, 60 x 60 cm, Stainless steel B1GCCOANOB









#### Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone

 $\sqrt{\rm CircoTherm^{@}}$  – Smart hot-air solution that lets you bake on up to three levels at once.

 $\sqrt{\text{LED-Display - simple, straightforward for clear reading}}$ 

#### Feature:

#### Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in Integrated Cleaning system : No

Required niche size for installation (HxWxD) :  $585-595 \times 560-568 \times 10^{-2}$ 

550 mm

Dimensions: 595 x 594 x 548 mm

Dimensions of the packed product (HxWxD) :  $675 \times 690 \times 660 \,$  mm

Control Panel Material: Stainless steel

Door Material : Glass Net weight : 31.639 kg Usable volume of cavity : 71 l

Cooking method : Conventional heat, Full width grill, Hot Air, Hotair

gentle, Hot air grilling First cavity material : Other Oven control : mechanical Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord: 120 cm

EAN code: 4242004234036 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A

Energy consumption per cycle conventional (2010/30/EC): 0.97

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.81 kWh/cycle

Energy efficiency index (2010/30/EC): 95.3 %

Connection rating: 2990 W Fuse protection: 13 A Voltage: 220-240 V Frequency: 50; 60 Hz Plug type: no plug





#### Features

#### Design

- LED Display (Red)
- Cavity inner surface: enamel grey

#### Features

- Control panel lock
- Interior halogen light

#### Cleaning

### Programmes/functions

• Cooling fan

## Accessories

• 1 x combination grid, 1 x universal pan

#### Performance/technical information

• Energy efficiency rating (acc. EU Nr. 65/2014): A Energy consumption per cycle in conventional mode: 0.97 kWh

Energy consumption per cycle in fan-forced convection mode:

0.81 kWh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre

- Total connected load electric: 2.99 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- $\bullet$  Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



# B1GCCOANOB

