BOSCH

Series 4, Fully-integrated dishwasher, 60 cm
SMV4HVX38G

Flexible loading and smart remote control of your dishwasher via the Home Connect app.

- **Home Connect**: home appliances with smart connectivity for an easier everyday life.
- **ExtraDry**: extra drying option for difficult-to-dry loads.
- **VarioFlex-baskets and VarioDrawer**: enhanced flexibility options with more space on all levels.
- **InfoLight**: a red light on the floor indicates whether the dishwasher is switched on or off.
- **Silence on demand**: up to 30 min noise reduction at any time via the Home Connect App.

Technical Data

Energy Efficiency Class: ....D
Energy Consumption for 100 cycles Eco Programme: .... 84 kWh
Maximum number of place settings: 13
The water consumption of the eco programme in liters per cycle: 9.5 l
Programme duration: .... 5:20 h
Airborne acoustical noise emissions : ....46 dB(A) re 1 pW
Airborne acoustical noise emission class: C
Installation type: ....Built-in
Height of removable worktop: ....0 mm
Dimensions of the product (HxWxD): ....815 x 598 x 550 mm
Min. required niche size for installation (HxWxD): ....815-875 x 600 x 550 mm
Depth with open door 90 degree: .... 1150 mm
Adjustable feet: .... Yes - all from front
Maximum adjustability feet: .... 60 mm
Adjustable plinth: ....Both horizontal and vertical
Net weight: ....34.3 kg
Gross weight: .... 36.5 kg
Connection rating: .... 2400 W
Fuse protection: ....10 A
Voltage: .... 220-240 V
Frequency: .... 50; 60 Hz
Length of electrical supply cord: ....175.0 cm
Plug type: ....GB plug
Length inlet hose: .... 165 cm
Length outlet hose: .... 190 cm
EAN code: 4242005304660
Installation type: ....Integrated

Optional accessories

SGZ0BI02   decorative strips stainless steel 81,5cm
SGZ1010   inlet and outlet hose extention
SGZ8BI00   Connection rail for divided furniture
SMZ2056   Attachment door, stainless steel
SMZ5003   Retractable hinge f. high corpus dimens.
SMZ5100   Vario-cutlery basket
SMZ5300   GlassSecure Tray

Series 4, Fully-integrated dishwasher, 60 cm
SMV4HVX38G

Flexible loading and smart remote control of your dishwasher via the Home Connect app.

[1] Scale of Energy Efficiency Classes from A to G

[2] Energy consumption in kWh per 100 cycles (in programme Eco 50 °C)

[3] Water consumption in litres per cycle (in programme Eco 50 °C)

[4] Duration of programme Eco 50 °C

Performance

- Energy Efficiency Class[1]: D
- Energy[2] / Water[3]: 84 kWh / 9.5 litres
- Capacity: 13 place settings
- Programme duration[4]: 5:20 (h:min)
- Noise level: 46 dB(A) re 1 pW
- Noise Efficiency Class: C

Programmes / functions

- 6 programmes: Eco 50 °C, Auto 45-65 °C , Intensive 70 °C, Express 65°, Glass 40 °C, Favourite
- Default favourite programme: Pre-Rinse
- 4 special options: Remote Start, Extra Dry, Half Load, SpeedPerfect+
- Machine Care
- Silence on Demand (via app)

Flexible design elements

- Vario Flex baskets
- Vario Drawer - loading of cutlery on 3rd level
- 3 stage Rackmatic height-adjustable top basket
- Low friction wheels on bottom basket
- Rack Stopper to prevent derailing of bottom basket
- 2 foldable plate racks in top basket
- 4 foldable plate racks in bottom basket
- Upper rack cup shelf

Innovations and technology

- Home Connect ready on WLAN
- Heat exchanger.
- DosageAssist detergent dispenser
- EcoSilence BLDC drive
- Automatic detergent detection
- AquaMix - Glass protection system

Design features

- Push button top edge controls
- InfoLight (Red) - Light projection on the floor
- Time delay (3, 6 or 24 hours)
- Acoustic end of cycle indicator, Time remaining indicator (min), water inlet indicator
- AquaStop: Bosch's warranty in case of water damage - for the lifetime of the appliance. Please find warranty terms under https://www.bosch-home.co.uk/customer-service/care-protection-and-parts/additional-warranties
- Self-cleaning filter system with 3 piece corrugated filter
- Large item spray head, steam protection plate
- Stainless steel/Polinox interior
- Dimensions (HxWxD): 81.5 x 59.8 x 55cm

Series 4, Fully-integrated dishwasher, 60 cm
SMV4HVX38G

measurements in mm

⊥ socket
( ) values with extension kit

measurements in mm